



Certificate

of Approval of Components and Systems

Holder of the Approval:

Sargent & Greenleaf Inc.
One Security Drive

US-40356 Nicholasville, Kentucky

This approval is valid only for the specified component/system as submitted for the test

- together with the parts listed in enclosure 1
- documented in the technical papers acc. enclosure 2
- for application in the specified fire protection and security installations. Use of the subject matter of the approval is subject to the hints/comments of enclosure 3.

The validity of the approval can be extended upon application. Application for extension shall be submitted six months before expiry of the current approval at the latest.

This certificate shall only be reproduced without any modifications and including all enclosures. All changes of the underlying conditions of this approval shall be reported at once to the VdS Certification Body enclosing the required documentation.

Any advertising with this VdS approved component/system shall reflect the correct contents of the certificate and shall not violate the competition regulations.

<i>Approval No.:</i>	<i>No. of pages:</i>	<i>Valid from:</i>	<i>Valid to:</i>
M 105335	4	18.04.2009	17.04.2013

Subject matter of the Approval:

High security electronic lock - class 2
Type 6129

Use:

in safes and strongrooms

Basis for approval:

Procedure for testing and the approval of equipment, components and systems used in fire protection and security technology - VdS 2344en : 2005-12

Performance of product surveillances - VdS 2841en : 2005-12

Rules for physical security devices
High security locks for secure storage units
Requirements and test methods - VdS 2396en : 2005-09

Secure storage units - Classification for high security locks according their resistance to unauthorized opening
EN 1300 : 2004-06

Cologne (Köln), 2009-04-16

Schüngel

Managing Director

ppa. Urban

Head of the VdS Certification Body

VdS Schadenverhütung GmbH
Zertifizierungsstelle
Amsterdamer Str. 174
D-50735 Köln

a company of the Gesamtverband
der Deutschen
Versicherungswirtschaft e.V.
(GDV)
accredited as a Certification Body
for fire protection and security
systems by the Deutschen
Akkreditierungsstelle Technik
(DATech)



DAT-ZE-005/92



To Certificate of Approval No. M 105335

Date 2009-04-16

The approved component/system comprises the following parts:

Description of component	Type	Applicant's Registration No.	Approval number of component (only complete for system approval)
Electronical high security lock for secure storage units Class 2 with input units with keypad extension	6129 61KP-2XX 6120-XXX 6101-202		

To Certificate of Approval No. M 105335

Date 2009-04-16

The approved component/system is described as follows:

Type of document	Manufacturer's identification	Date	Number of Pages
Bill of material lock	6129-200 Bill of Material.xls	26.07.2004	1
List of parts drawings with the parts drawings mentioned in the bills of material	6128_29 Drawing List.xls	27.07.2004	2
Installation instructions for lock 6129	630-610_6129_install.pdf	13.12.2004	6
Technical data sheet	S&G-121 TDS 630-693 German.doc	22.03.2005	1
Programmer and user instructions for 6128/6129	630-600_full_op_6128_6129 GER.pdf	18.03.2005	32
Installation instructions input unit	630-614	07.08.2001	
Instructions for battery change	630-615	02.02.2001	
Prüfberichte der VdS-Laboratorien	STM 02 805	25.01.2002	
	1. addendum to STM 02 805	15.04.2005	
	SW-2000311	29.11.2001	
	SW-2004306	12.11.2004	



Enclosure 3

Sheet 1

To Certificate of Approval No.: M 105335

Date 2009-04-16

Instructions for the application of the approval component/system (see enclosure 1):

1. When mounting the installation instructions of the manufacturer have to be followed. It is has to be considered that the lock is protected sufficient against forced attack.
2. Locks of type 6129 of company Sargent & Greenleaf, Inc. are covered by this certificate only, if they are marked with the manufacturer's name or logo, type description and VdS label according to VdS 2344.
3. The locks fulfill the requirements of EN 1300 - class B.